



LSB-D12 SUBWOOFER



E L E C T R O N I C A R C H I T E C T U R E

LSB-D12 SUBWOOFER

The E-cooustic Systems LSB-D12 is a high-output subwoofer system designed to provide high fidelity, low frequency audio reproduction from a relatively small enclosure. The LSB-D12 provides exceptionally linear low frequency extension that integrates seamlessly with E-cooustic Systems full range loudspeakers. This is particularly important for systems that utilize a pipe organ, or when a venue lacks sufficient low frequency information. The LSB-D12 is provided with a flat black painted finish and a black coated steel grille.

SPECIFICATIONS

System Type:
INFRA Sealed chamber
(2.9 cu. ft.)

Impedance:
4 Ohms

Crossover Network:
Requires INFRA Integrator

Frequency Response:
8 Hz to 95 Hz +/-3 dB
(2 pi Steradians, with 8 Hz Integrator)

Sensitivity:
95 dB SPL @ 80 Hz (1W @ 1m)

Power Handling:
400 W continuous sine wave
400 W instantaneous peak

Finish:
Black paint

Dimensions:
28"h x 18"w x 15"d
72 cm x 46 cm x 39 cm

Weight:
69 lbs.
32 kg

Shipping Dimensions:
18" x 30" x 21"
46 cm x 77 cm x 54 cm

Shipping Weight:
77 lbs.
35 kg