



L  
S  
B  
-  
S  
1  
2  
  
S  
U  
B  
W  
O  
O  
F  
E  
R

The E-coustic Systems LSB-S12 is a compact subwoofer system designed to provide high fidelity, low frequency audio reproduction. The LSB-S12 provides exceptionally linear low frequency extension that integrates seamlessly with E-coustic Systems full range loudspeakers. This is particularly important for systems that utilize a pipe organ, or when a venue lacks sufficient low frequency information. The LSB-D12 is provided with a flat black painted finish and a black coated steel grille.

# LSB-S12 SUBWOOFER



E L E C T R O N I C A R C H I T E C T U R E

## SPECIFICATIONS

### System Type:

INFRA Sealed chamber  
(1.4 cu. ft.)

### Frequency Response:

8 Hz to 95 Hz +/-3 dB  
(2 pi Steradians, with  
8 Hz Integrator)

### Sensitivity:

92 dB SPL @ 80 Hz (1W @ 1m)

### Impedance:

8 Ohms

### Power Handling:

200 W continuous sine wave  
200 W instantaneous peak

### Input Connectors:

Cinch 142 screw terminal  
barrier strip

### Low Frequency Transducers:

12" INFRA cone  
2.5" Voice coil  
80 oz. Magnet

### Grille:

16 Gauge black vinyl coated perforated steel

### Optional Hardware:

Rigging points

### Enclosure:

18 mm 13-ply birch plywood

### Finish:

Black paint

### Dimensions:

15" h x 18" w x 15" d (39 cm x 46 cm x 39 cm)

### Weight:

39 lbs (18 kg)

### Shipping Dimensions:

18" x 21" x 18" (46 cm x 54 cm x 46 cm)

### Shipping Weight:

44 lbs. (20 kg)