

Ottocanali 4K4

Level	Load	Rated power	230 V AC Mains				115 V AC Mains				Thermal dissipation	
			Current draw (A)	WATT OUT	WATT IN	DISSIPATED	Current draw (A)	WATT OUT	WATT IN	DISSIPATED	BTU/h	kcal/h
Idle			0.8	0	35	35	0.6	0	30	30	118	30
Pink noise (1/8 rated power)	2Ω per channel	8 x 450 W	3.5	430	695	265	6.2	425	695	270	920	232
	2.7Ω per channel	8 X 450 W	3.6	450	688	238	6.1	448	682	234	811	205
	4Ω per channel	8 X 500 W	3.9	506	752	246	6.6	502	737	235	839	211
	8Ω per channel	8 X 250 W	2.6	249	410	161	3.6	249	393	144	549	138
Pink noise (1/4 rated power)	2Ω per channel	8 x 450 W	6.1	860	1294	434	11.5	850	1314	464	1583	399
	2.7Ω per channel	8 X 450 W	6.4	900	1281	381	11.4	896	1289	393	1339	338
	4Ω per channel	8 X 500 W	6.9	1012	1405	393	12.3	1004	1397	393	1340	338
	8Ω per channel	8 X 250 W	4.3	498	742	244	6.4	498	722	224	830	209

Ottocanali 8K4

Level	Load	Rated power	230 V AC Mains				115 V AC Mains				Thermal dissipation	
			Current draw (A)	WATT OUT	WATT IN	DISSIPATED	Current draw (A)	WATT OUT	WATT IN	DISSIPATED	BTU/h	kcal/h
Idle			0.8	0	35	35	0.6	0	30	30	118	30
Pink noise (1/8 rated power)	2Ω per channel	8 × 850 W	6.1	854	1290	436	11.7	848	1288	440	1500	378
	2.7Ω per channel	8 × 850 W	5.9	838	1234	396	11.0	842	1242	400	1364	344
	4Ω per channel	8 × 1000 W	6.6	981	1422	441	12.6	992	1426	434	1504	379
	8Ω per channel	8 × 600 W	4.3	598	889	291	8.1	598	892	294	1002	253
Pink noise (1/4 rated power)	2Ω per channel	8 × 850 W	11.3	1708	2499	791	22.6	1696	2527	831	2834	714
	2.7Ω per channel	8 × 850 W	10.93	1676	2388	712	21.3	1684	2435	751	2561	646
	4Ω per channel	8 × 1000 W	12.3	1962	2760	798	24.5	1984	2803	819	2793	704
	8Ω per channel	8 × 600 W	7.7	1196	1705	509	15.4	1196	1735	539	1838	463

Ottocanali I2K4

Level	Load	Rated power	230 V AC Mains				115 V AC Mains				Thermal dissipation	
			Current draw (A)	WATT OUT	WATT IN	DISSIPATED	Current draw (A)	WATT OUT	WATT IN	DISSIPATED	BTU/h	kcal/h
Idle			0.8	0	35	35	0.6	0	30	30	118	30
Pink noise (1/8 rated power)	2Ω per channel	8 × 1000 W	7.1	1000	1510	510	13.5	1002	1497	495	1739	439
	2.7Ω per channel	8 × 1000 W	7.0	993	1475	482	13.1	999	1445	446	1644	414
	4Ω per channel	8 × 1500 W	9.7	1487	2115	628	18.5	1507	2075	568	2141	540
	8Ω per channel	8 × 850 W	6.0	864	1260	396	12.3	869	1263	394	1350	340
Pink noise (1/4 rated power)	2Ω per channel	8 × 1000 W	13.4	2000	3020	1020	26.3	2004	2994	990	3478	877
	2.7Ω per channel	8 × 1000 W	13.1	1986	2950	964	25.4	1998	2890	892	3287	829
	4Ω per channel	8 × 1500 W	18.6	2974	4230	1256	36.3	3014	4150	1136	4283	1080
	8Ω per channel	8 × 850 W	11.2	1728	2520	792	23.8	1738	2526	788	2701	681